

Klübersynth CH 2-280

Special high-temperature oil for sliding chain systems in film stretchers made by Brückner Maschinenbau



Your benefits at a glance

- Especially developed for medium to high chain speeds and high stretching temperatures
- High oxidation stability leading to low oil consumption
- Easy machine maintenance due to low residue formation
- Long chain life due to low wear rate
- Cost-efficient product due to good price-performance ratio

Your requirements - our solution

Most film stretchers are operated over three shifts without stoppage. Any downtime required for maintenance or due to malfunction comes at the expense of plant productivity; the chain oil used has a major influence on these factors. Varnish build-up can prevent penetration of sufficient lubricant to the friction points of the chain pins and the guide rail. This leads to higher friction, requiring more lubricant. This will in turn lead to further contamination making premature cleaning of the whole machine (transverse direction orienter) necessary - a costly and time-consuming procedure. Our aim is therefore to extend your maintenance intervals and reduce the cost of maintenance operations.

Our profound expertise in the development of high-temperature chain oils is based on 40 years of experience gained in collaboration with leading OEMs and film stretcher operators.

Klüber Lubrication cooperated with Brückner Maschinenbau to develop Klübersynth CH 2-280 for the specific requirements of their sliding chain systems in biaxial film stretchers. Consequently, this lubricant is a vital factor for the profitable operation of these machines. The special combination of ester oils and additives produces only a minimum of residues and shows high thermal resistance. This means the used chain oil can flow off better, keeping the chain system clean. Cleaning intervals can be extended and operating costs are reduced. Another effect of the special additives is lower wear at the friction points and hence longer chain life.

With its good price-performance ratio, Klübersynth CH 2-280 offers film stretcher operators high machine availability at low cost. This makes it the most economical product in our successful series of chain oils.

Application

Klübersynth CH 2-280 is a fully synthetic high-temperature oil that was especially developed for the requirements of conveyor chain sliding systems and pins in biaxial high-speed film stretchers. Oven temperatures may be higher than 200 °C in these applications. The machine may run at speeds up to 625 m/min.

Application notes

Klübersynth CH 2-280 is miscible with all Klüber Lubrication chain oils offered for biaxial film stretchers, except PRIMIUM FLUID SPECIAL. It is therefore not necessary to use a special cleaning or flushing oil for an oil changeover. We recommend, however, cleaning the chain system and all machine parts in contact with the oil before filling with the new lubricant so that it can release its full benefits. For this purpose, we recommend using our chain cleaning and flushing oil Klübersynth CZ 2-85.

When changing over from chain oils made by other manufacturers, please ask for advice.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes

Klübersynth CH 2-280

Canister 5 l

+

Klübersynth CH 2-280

Special high-temperature oil for sliding chain systems in film stretchers made by Brückner Maschinenbau



Pack sizes	Klübersynth CH 2-280
Canister 20 l	+
Drum 200 l	+
Characteristics	Klübersynth CH 2-280
Article number	067071
Composition, type of oil	ester oil
Appearance	clear
Colour space	orange
Service temperature, lower limit	0 °C
Service temperature, upper limit	250 °C
Density, DIN 51757, 20°C	approx. 0.97 g/cm ³
Flash point, DIN EN ISO 2592, Cleveland open cup	≥ 250 °C
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 100°C	approx. 24 mm ² /s
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 280 mm ² /s
Viscosity index, DIN ISO 2909	≥ 100
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 95 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.