

# Klübersynth G 4

Synthetic high-performance gear oil



## Your benefits at a glance

- Sufficient scuffing protection
- Good wear protection
- Excellent ageing and oxidation resistance
- Wide service temperature range due to good viscosity-temperature behaviour
- Low foaming tendency
- Energy savings due to optimised friction behaviour
- Very good protection of nonferrous metals

## Your requirements - our solution

Klübersynth G 4 is a synthetic high-performance gear oil based on polyalphaolefin and selected additives.

Klübersynth G 4 shows high scuffing strength. Gears are sufficiently protected against scuffing even at extremely high peak loads, vibrations or oscillations. The good wear protection of the gear components ensures that their calculated service life is achieved, leading to lower maintenance and repair costs.

Klübersynth G 4 offers a much longer service life than mineral oils due to its excellent ageing and oxidation resistance; thus service intervals can be extended and maintenance costs reduced. The product's low foaming tendency and anti-corrosive properties enable problem-free gear operation. Klübersynth G 4 is neutral towards most sealing materials such as NBR or FKM. Oil leakage leading to contamination is prevented. Due to the product's good compatibility with brass, bronze and copper, it may be used for the lubrication of applications where the corrosion of nonferrous metals is an issue.

The good viscosity-temperature behaviour supports the formation of a sufficient lubricant film across a wide service temperature range. Therefore, a single viscosity grade can cover both low and high temperatures in many applications.

The optimised friction behaviour enabled by the carefully selected base oils reduces power loss and improves gear efficiency.

Klübersynth G 4 is recommended and approved for ITEMA / Somet weaving machines as well as gearboxes from Stäubli and Yilmaz Redüktör.

By using Klübersynth G 4 you can benefit from a number of advantages that will help you save costs easily and efficiently. We look forward to hearing from you.

## Application

Klübersynth G 4 was especially developed for the lubrication of spur, bevel and planetary gears. It can also be used for plain and rolling bearings.

## Application notes

Klübersynth G 4 can be used for immersion, immersion circulation and injection lubrication.

The use of drip-feed oilers, brushes, oil cans or suitable automatic lubricating systems is also possible. When using automatic lubricating systems, please note the manufacturer's instructions regarding the maximum permissible viscosity. The low-viscosity varieties are also used for oil mist lubrication.

Klübersynth G 4 is miscible with mineral oils. However, for the Klübersynth G 4 oil to deliver its full performance, any residues of a previously used mineral oil should not exceed 5 % in quantity.

For use at permanent temperatures of 80 °C max., seals made of NBR may be used. For higher temperatures, seals made of FKM should be chosen. It should be noted that elastomers from one or several manufacturers can behave differently; therefore tests should be performed.

For checking the contact pattern during running-in, the inspection paint Klübertop P 39-462 Spray (Art. No. 081295) can be used.

## Material safety data sheets

Material safety data sheets can be requested via our website [www.klueber.com](http://www.klueber.com). You may also obtain them through your contact person at Klüber Lubrication.

# Klübersynth G 4

Synthetic high-performance gear oil



## Viscosity selection

When determining the oil viscosity for gear lubrication, the gear manufacturer's instructions take priority. To determine the correct oil viscosity for bearings, please observe the bearing manufacturer's instructions.

Due to the better viscosity-temperature behaviour of Klübersynth G 4, its actual viscosity during operation differs from that of mineral oils and can be determined by means of the enclosed diagram.

Pack sizes	Klübersynth G 4-68	Klübersynth G 4-130	Klübersynth G 4-150	Klübersynth G 4-220
Bucket 19 l	+	+	+	+
Drum 208 l	+	+	+	+

Characteristics	Klübersynth G 4-68	Klübersynth G 4-130	Klübersynth G 4-150	Klübersynth G 4-220
Article number	012186	012024	012285	012301
Colour space	yellow	yellow	yellow	yellow
Service temperature, lower limit	-40 °C	-40 °C	-40 °C	-40 °C
Service temperature, upper limit	140 °C	140 °C	140 °C	140 °C
Density, DIN 51757, 20°C	approx. 0.86 g/cm <sup>3</sup>	approx. 0.86 g/cm <sup>3</sup>	approx. 0.86 g/cm <sup>3</sup>	approx. 0.87 g/cm <sup>3</sup>
Flash point, DIN EN ISO 2592, Cleveland open cup	≥ 200 °C	≥ 200 °C	≥ 200 °C	≥ 230 °C
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 100°C	approx. 10 mm <sup>2</sup> /s	approx. 17 mm <sup>2</sup> /s	approx. 19 mm <sup>2</sup> /s	approx. 26 mm <sup>2</sup> /s
Kinematic viscosity, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 68 mm <sup>2</sup> /s	approx. 130 mm <sup>2</sup> /s	approx. 150 mm <sup>2</sup> /s	approx. 220 mm <sup>2</sup> /s
Viscosity index, DIN ISO 2909	≥ 115	≥ 130	≥ 130	≥ 140
Copper corrosion, DIN EN ISO 2160, 24 h, 100°C	1 - 100 - 24 corrosion degree	1 - 100 - 24 corrosion degree	1 - 100 - 24 corrosion degree	1 - 100 - 24 corrosion degree
Pour point, DIN ISO 3016, ASTM D97, ASTM D5950, ASTM D7346	≤ -40 °C	≤ -40 °C	≤ -40 °C	≤ -40 °C
FZG scuffing test, DIN ISO 14635-1, A / 8.3 / 90, failure load stage	≥ 12	≥ 12	≥ 12	≥ 12
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months	36 months

# Klübersynth G 4

Synthetic high-performance gear oil



---

## Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 95 years.

Klüber Lubrication München GmbH & Co. KG /  
Geisenhausenerstraße 7 / 81379 München / Germany /  
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.