

Klübersynth UH1 64-62

Synthetic lubricating grease suitable for use in the food-processing and pharmaceutical industries



Your benefits at a glance

- Less maintenance due to good resistance to low and high temperatures, synthetic base oil for extended relubrication intervals and good resistance to water
- ISO 21469 certified - supports the compliance with the hygienic requirements in your production. You will find further information about ISO Standard 21469 on our website www.klueber.com.

Your requirements - our solution

Klübersynth UH1 64-62 shows a good low- and high-temperature behaviour, and good resistance to water, corrosion, ageing and oxidation.

Klübersynth UH1 64-62 is NSF H1 registered and therefore complies with FDA 21 CFR § 178.3570. The lubricant was developed for incidental contact with products and packaging materials in the food-processing, cosmetics, pharmaceutical or animal feed industries. The use of Klübersynth UH1 64-62 can contribute to increase reliability of your production processes. We nevertheless recommend conducting an additional risk analysis, e.g. HACCP.

Application

Klübersynth UH1 64-62 is suitable for lubrication points in machines and installations used in the food-processing and pharmaceutical industries, particularly for all points where contact between the lubricant and the food product cannot be excluded. We recommend lubricating all friction points with Klübersynth UH1 64-62 in order to avoid negative effects caused by lubricant spreading.

MOSH-MOAH Hint

The chromatographic measurement of MOSH can also detect saturated hydrocarbons of form other sources than mineral oil so it may be possible for chromatographic MOSH peaks to be detected in some Klüber Lubrication H1 products.

Application notes

Klübersynth UH1 64-62 is applied by brush, spatula, grease gun or grease cartridge. Before using Klübersynth UH1 64-62 to replace other greases, the bearings should be cleaned thoroughly. Grease exchange by relubrication is sufficient if the greases are miscible.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübersynth UH1 64-62
Cartridge 400 g	+
Can 1 kg	+
Bucket 25 kg	+
Characteristics	Klübersynth UH1 64-62
Article number	096046
Composition, thickener	silicate
Composition, type of oil	ester oil , synthetic hydrocarbon oil

Klübersynth UH1 64-62

Synthetic lubricating grease suitable for use in the food-processing and pharmaceutical industries



Characteristics	Klübersynth UH1 64-62
Mineral Oils associated with MOSH (Mineral Oil Saturated Hydrocarbons) / MOAH (Mineral Oil Aromatic Hydrocarbons), (Information based on recipe. The presence of impurities, cannot be ruled out.)	Not intentionally added
Colour space	beige
Texture	homogeneous
Service temperature, lower limit	-40 °C
Service temperature, upper limit	140 °C
NSF H1 registration number	136871
Density, Klüber method: PN 024, 20°C	approx. 0.93 g/cm ³
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	265 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	295 0.1 mm
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s ⁻¹	approx. 3000 mPas
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 100°C	approx. 10 mm ² /s
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 65 mm ² /s
Flow pressure, DIN 51805-2, -40°C	≤ 1400 mbar
Dropping point, DIN ISO 2176 / IP 396	≥ 250 °C
Speed factor (n x dm)	approx. 500000 mm/min
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 95 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.