

DRAWTEX PRB-90**YELLOW METAL COLD DRAWING OIL****PRODUCT DESCRIPTION**

It is drawing oil which has been formulated with special lubricants, highly refined base oils, anticorrosion, antiwear and EP additives. It is used for processing of yellow metals.

APPLICATION / USAGE

It is especially used for cold drawing operations of yellow metals such as copper, brass and etc. in addition it can be used for other drawing operations. It forms very durable film layer and it is resistant to high loads in very difficult forming operations.

It is used as pure and applied by brush or roller. It can be easily removed by alkaline or neutral cleaners.

ADVANTAGES / BENEFITS

- Provides superior surface quality due to its excellent lubrication ability and special additives,
- Increases production efficiency, provides a decline of unit costs,
- Does not splash and pollute the environment, when it is applied by roller,
- Removes the heat generated during the operation,

- Even under difficult conditions can maintain performance characteristics,
- Thanks to its liquid form, it can be applied easily even for more difficult operations,
- The lubricating film layer on the material surface protects the material from rust for a while,
- Can be easily removed by alkaline or neutral cleaners,
- Improves mold life after the operations,
- Provide long life and perfect equipment protection.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
Appearance	Yellow, Clear	-
Kinematic Viscosity (40°C, cSt)	90-110	ASTM D 445
Flash Point (°C)	230	ASTM D 92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2022.01.01

