

PRODUCT DATA

Metalstar ASW-102

Anti-Solder Paste

Description

Metalstar ASW-102 is a specially blended product to facilitate the removal of solder, which is formed during high pressure die-casting of aluminium. It is formulated as an easy to use paste.

Metalstar ASW-102 forms an adherent bond with the solder and dislodges it from the tool steel during the subsequent shots.

Benefits

- Improved productivity due to reduced time for solder removal
- Reduced costs due to lower scrap
- Adherent paste reduces consumption and wastage.

Typical Properties

Appearance	Black paste
Odour	Mildly acidic
Flash Point	Not applicable
Storage Stability, unopened container	24 months

Application

Apply Metalstar ASW-102 with a wire or bristle brush.

Solder Removal:

- Apply a minimum amount of Metalstar ASW-102 to the solder accumulation and to the die steel in the vicinity of the solder.
- 2. Follow with your normal spray pattern of die lubricant.
- 3. Make your normal shot.
- 4. The solder will be dislodged with the casting.
- Repeated applications of Metalstar ASW-102 may be necessary to treat very stubborn solder areas.

Storage

Metalstar ASW-102 should be stored at ambient temperatures of less than 40° C.

Handling

We believe Metalstar ASW-102 has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Material Safety Data Sheet.

Packaging

Metalstar ASW-102 is available in 25 kg and 1 kg containers.

Further Information

Request information on our complete range of materials for this industry.

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. Chem-Trend warrants only that it's products will meet it's sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are requested to check that they are in possession of the latest version of this document and Chem-Trend is at their disposal to supply any additional information.

Edition: 10.01.07

Chem-Trend (Deutschland) GmbH = Robert-Koch-Str. 27 = 22851 Norderstedt = Phone: +49-40-529 55-0 = Fax: +49-40-529 55-2111