

Technical Data Sheet





Description

NYLSET BLU is extremely concentrated liquid detergent formulated for most advanced efficiency of cleaning and security of use even in the most difficult working conditions. NYLSET BLU is therefore specific for use in extreme conditions where is not possible to obtain satisfactory results with other valid products. Powerful formulation permits even to remove tar and asphalt film. If used in correct concentration this product absolutely does not damage painted parts, on the contrary this parts will be renewed. NYLSET BLU have to be used with caution on light alloys, where is recommended to test first the product on parts which are not in sight. NYLSET BLU is not flammable product and has to be always diluted in water following to recommended ratio. NYLSET BLU does not leave residuals on treated surfaces and is biodegradable over 90%.

Use / application

NYLSET BLU can be used manually, with nebuliser (mist blower), with hydraulic jet cleaner, with brush washer, floor washing machines etc. In case of extremely dirty surfaces it is recommended to apply product and leave it to act for few minutes and therefore rinse out with water.

Properties

Dilution Ratios

Engines washing 1:10

Degreasing of steel structural works from 1:10 to 1:20

Floor washing from 1:20 to 1:30

Cars and motorbikes washing 1:100

Boats washing (gel-coat) 1:20

Boats washing (bilge) 1:4

Earthmoving machinery and fork lifts washing from 1:50 to 1:100

Paint renewing earthmoving equipment and forklifts from 1:4 to 1:3

Sludge degreasing in tanks from 1:10 to 1:7 (better with warm water)

Extremely dirty workshop floor renewing 1:10 (better with warm water)

To remove tires signs on the floor from 1:10 to 1:5

Technical Data

Density at 15°C	ASTM D1122	g/cm³	1.1
pH (pure)	DIN 51369		12